DEFINE FGID SUBSTITUTION TABLE

The Define FGID Substitution Table option allows the System Administrator to define the FGID to use when the desired FGID is not found in the Font Global ID Table. The Administrator can define ranges, or specific FGID from/to values. A specific match takes precedence over a range match.

Select **F6** to add a new entry. Enter The following screen should appear:

Spool PDF Overlay/400 (TM) Add/Copy FGID Specification
FGID Spec to Add/Copy -
Type: (R, S)
From FGID: 0
To FGID: 0
F3=Exit F12=Cancel Current Operation

The above parameters have the following definitions:

Type

Specifies the entry type. Specify one of the following:

R (**Range**): A range is being specified. The From and To FGIDs will be specified.

S (Specific): A single, specific From FGID will be specified. The To FGID field will be ignored.

From FGID

Specify the Range lower limit (for type R) or From (for type S) FGID.

To FGID

Specify the Range upper limit (for type R) FGID. This parameter will be ignored for type S.

Press ENTER. The following screen should appear:

SPOOL PDF OVERLAY/400TM

Spool PDF Overlay/400 (TM	
Define FGID Substitution Ta	able 16:43:27
Type: R From FGID: 1 To FGID:	2
Substitute FGID: 33	
Substitute Option: <u>0</u>	(0=Always, 1=Not Found)
F3=Exit F4=Prompt F12=Cancel Current Operation	

The above parameters have the following definitions:

Substitute FGID

Specifies the FGID to substitute. A definition for this FGID must exist in the Font Global ID table.

Substitute Option

Specifies when to perform the FGID substitution. Specify one of the following:

0 (Always): Substitution will always occur.

1 (Not Found): Substitution will only occur if the source FGID was not found in the FGID Specs table.